

FL-08

Cross-ply pneumatic – medium intensity applications

Material Handling Cross-ply tires



Mitas FL-08

Delivers optimum performance for medium intensity applications.

Key product features


Block tread design – Improves traction performance

Enhanced stability – Pattern specifically designed to improve directional stability


Shock absorbance – Heavy-duty service



STABILITY



TIRE LIFE



COOL RUNNING

Technical data and load capacities

Tire size (Alternative size)	Type	Rim (permitted)	Section width (inch)	Outer diameter (inch)	Minimal dual spacing (inch)	Tread depth (32nd)	Tire weight (lbs)	Service description LI/SS	Ply rating PR	Tire load (lbs) Counterbalanced Lift trucks up to 16 mph		Tire pressure (psi)
										Load wheel	Steering wheel	
4.00 - 8	TT	3 1/4-8	4.4	16.3	5.4	13	10	94 A5 97 A5	8 PR 10 PR	1,920 2,090	1,480 1,610	131 145
15 x 4.5 - 8	TT	3.00D-8	4.6	15.0	5.5	10	9	100 A5	12 PR	2,290	1,760	145
5.00 - 8	TT	3.00D-8	5.2	18.4	6.2	14	12	106 A5 111 A5	8 PR 10 PR	2,720 3,120	2,090 2,400	120 145
16 x 6 - 8 (150/75-8)	TT	4.33R-8	6.0	16.7	6.9	15	12	113 A5	16 PR	3,300	2,540	145
18 x 7 - 8 (180/70-8)	TT	4.33R-8	6.8	18.2	7.8	18	18	121 A5 125 A5	14 PR 16 PR	4,160 4,730	3,200 3,640	131 145
6.00 - 9	TT	4.00E-9	6.3	21.3	7.6	16	18	118 A5 121 A5	10 PR 12 PR	3,780 4,160	2,910 3,200	123 145
21 x 8 - 9 (200/75-9)	TT	6.00E-9	7.9	21.1	9.1	19	27	131 A5 134 A5	14 PR 16 PR	5,590 6,070	4,300 4,680	131 145
6.50 - 10	TT	5.00F-10 (5.50F-10)	7.0	23.2	8.4	18	23	122 A5 125 A5 128 A5	10 PR 12 PR 14 PR	4,300 4,730 5,160	3,300 3,640 3,960	112 131 145
7.50 - 10	TT	5.00F-10	8.1	25.3	9.5	19	32	133 A5	12 PR	5,910	4,540	116
23 x 9 - 10 (225/75-10)	TT	6.50F-10	8.9	23.4	10.2	20	33	142 A5	20 PR	7,360	5,840	145
7.00 - 12	TT	5.00S-12	7.6	26.5	9.1	19	35 (12PR) 37 (14PR) 41 (16)	133 A5 134 A5 136 A5	12 PR 14 PR 16 PR	5,910 6,070 6,420	4,540 4,680 4,940	123 131 145
23 x 10 - 12	TT	8.00G-12	9.6	23.4	11.5	25	49	139 A5	16 PR	6,970	5,360	116
27 x 10 - 12 (250/75-12)	TT	8.00G-12	10.3	26.8	11.5	23	48	143 A5 146 A5 152 A5	14 PR 16 PR 20 PR	7,820 8,600 10,180	6,000 6,600 7,850	102 116 145
7.00 - 15	TT	5.50-15	7.8	29.5	9.3	21	45	140 A5	14 PR	7,170	5,520	134
7.50 - 15	TT	6.0-15 (6.5-15)	8.4	30.4	10.0 (10.2)	26	55	144 A5 146 A5	14 PR 16 PR	8,030 8,600	6,150 6,600	134 145
8.15 - 15 (28 x 9-15)	TT	7.0-15	8.5	27.9	9.8	23	44	146 A5	14 PR	8,600	6,600	145
8.25 - 15	TT	6.5-15	9.2	32.9	11.1	29	71	149 A5 153 A5	14 PR 18 PR	9,320 10,460	7,150 8,050	116 145
250 - 15 (250/70-15)	TT	7.50-15	9.9	29.0	11.3	25	55	153 A5 155 A5	18 PR 20 PR	10,460 11,110	8,050 8,550	138 145
28 x 12.5 - 15	TT	9.75-15	10.8	28.6	12.8	21	76	140 A5	20 PR	10,000	7,600	131
300 - 15 (315/70-15)	TT	8.00-15	11.8	33.1	13.6	29	86	164 A5 165 A5	20 PR 22 PR	14,330 14,760	11,000 11,400	131 145

© Yokohama TWS-08/2023//MAGIC7 | Subject to technical amendments, printing errors and mistakes in text or illustrations.

mitas-tires.com