SFT – Technical data and load capacities (Continuation)

Tire size Service description LI/SS	Permitted rims*	Tire section width (inch)	Tire outer dia-meter (inch)	Static loaded radius (inch)	Rolling circum-ference (inch)	Tread depth (32nd)	RCI	Flat plate (sq. inch)	Number of lugs x 2	Tire weight (lbs)	Tire load capacity (lbs) at tire pressure (psi)										Speed (mph)
											9	12	15	17	20	23	29	35	41	47	
900/60 R 32 181 A8 (178 B)	**DW 27 B** DW 30 B	33.7 35.0	75.2	33.5	224.4	71	47	543	22	772			9,370	10,250	11,070	12,020	13,120	14,330	15,490	**16,500**	31
											8,580	9,510	10,300	11,270	12,160	13,230	14,410	15,660	17,020	**18,200**	25
											9,180	10,180	11,030	12,050	13,010	14,160	15,420	16,750	18,210	19,470	19
											9,530	10,560	11,430	12,500	13,490	14,690	16,000	17,380	18,900	20,200	16
											10,560	11,700	12,670	13,860	14,960	16,270	17,730	19,260	20,940	22,380	12
											11,160	12,370	13,380	14,640	15,810	17,200	18,730	20,350	23,480	25,470	6
											12,440	13,790	14,930	16,340	17,630	19,180	20,890	22,700	24,680	26,380	9 Cycl
900/70 R 32 188 A8 (185 B)	**DW 27 B** DW 30 B	35.2 36.4	80.7	35.3	238.2	81	48	651	17	805			11,150	12,190	13,360	14,770	15,910	17,090	18,560	**20,400**	31
											10,180	11,290	12,250	13,410	14,690	16,100	17,470	18,740	20,400	**22,000**	25
											10,890	12,080	13,110	14,340	15,710	17,220	18,700	20,050	21,820	23,590	19
											11,300	12,540	13,590	14,880	16,310	17,870	19,400	20,800	22,630	24,480	16
											12,510	13,890	15,060	16,480	18,070	19,800	21,500	23,050	25,080	27,120	12
											13,230	14,690	15,920	17,430	19,100	20,930	22,720	24,370	26,520	28,670	6
											14,750	16,370	17,760	19,440	21,290	23,340	25,340	27,180	29,580	31,970	9 Cycl
1050/50 R 32 178 A8 (178 B)	**36.00 VA**	40.0	74.4	33.7	222.0	76	46	736	16	1,008			11,120	12,160	13,130	14,330	15,560	**16,500**			31
											9,260	10,260	11,120	12,160	13,130	14,330	15,560	**16,500**			25
											9,910	10,990	11,900	13,010	14,050	15,340	16,650	17,700			19
											10,290	11,400	12,340	13,490	14,580	15,910	17,270	18,360			16
											11,400	12,630	13,670	14,960	16,140	17,630	19,140	20,340			12
											12,050	13,350	14,450	15,810	17,070	18,630	20,230	21,500	24,810		6
											13,430	14,880	16,130	17,630	19,040	20,780	22,560	23,980	26,650		9 Cycl
1250/50 R 32 188 A8 (185 B)	**44"** 40"	48.0 46.5	79.5	35.0	236.2	81	48	884	17	1,259			12,470	13,810	15,350	17,090	18,740	**20,400**			31
											10,430	12,160	13,690	15,180	16,870	18,740	20,590	**22,000**			25
											11,160	13,020	14,650	16,020	18,050	20,050	22,040	23,590			19
											11,580	13,510	15,200	16,850	18,720	20,800	22,870	24,480			16
											12,820	14,960	16,850	18,680	20,750	23,050	25,340	27,120			12
											14,600	17,030	19,170	21,260	23,620	26,240	28,830	30,870			6
											15,130	17,630	19,860	22,020	24,460	27,180	29,870	31,970	35,280		9 Cycl
1250/50 R 32 194 A8 (191 B)	**44"** 40"	46.5 48.0	79.5	35.0	236.2	81	48	891	17	1,280		11,070	12,470	13,810	15,350	17,090	18,740	20,400	22,140	**24,000**	31
											10,430	12,160	13,690	15,180	16,870	18,740	20,590	22,050	24,330	**26,000**	25
											11,160	13,020	14,650	16,020	18,050	20,050	22,040	23,590	26,030	27,840	19
											11,580	13,510	15,200	16,850	18,720	20,800	22,870	24,480	27,000	28,890	16
											12,820	14,960	16,850	18,680	20,750	23,050	25,340	27,120	29,920	32,010	12
											14,600	17,030	19,170	21,260	23,620	26,240	28,830	30,870	34,060	36,430	6
											15,130	17,630	19,860	22,020	24,460	27,180	29,870	31,970	35,280	37,730	9 Cycl
650/60 R 34 159 D (162 A8)	**DW 20 B** DW 21 B DW 23 B	25.6 26.0 26.8	64.5	29.1	194.3	71	43	374	19	474			6,160	6,740	7,400	8,050	8,910	**9,650**			40
												5,830	6,470	7,080	7,770	8,460	9,350	10,130			31
											5,360	6,070	6,750	7,380	8,100	8,820	9,750	**10,500**			25
											5,620	6,380	7,090	7,750	8,510	9,260	10,240	11,090			19
											6,850	7,770	8,630	9,440	10,360	11,270	12,470	13,510	14,480		6
											4,520	5,140	5,700	6,230	6,840	7,440	8,220	8,920			31 Dual
650/65 R 34 161 D (164 A8)	**DW 20 B** DW 21 B DW 23 B	26.1 26.5 27.3	67.7	30.3	201.4	71	45	377	19	506			7,090	7,660	8,140	8,540	9,490	**10,200**			40
												6,770	7,440	8,040	8,540	8,970	9,970	10,710			31
											6,280	7,070	7,760	8,380	8,910	9,370	10,390	**11,000**			25
											6,600	7,420	8,150	8,810	9,360	9,820	10,910	11,730			19
											8,040	9,030	9,920	10,720	11,390	11,960	13,290	14,280	15,300		6
											5,300	5,950	6,550	7,080	7,520	7,890	8,780	9,420			31 Dual
710/60 R 34 164 D (167 A8)	**DW 23 B**	27.6	66.9	30.3	199.2	76	45	386	18	514			7,070	7,730	8,420	9,100	10,200	**11,000**			40
												6,680	7,420	8,110	8,840	9,480	10,710	11,580			31
											6,140	6,970	7,740	8,460	9,230	9,920	11,160	**12,000**			25
											6,450	7,320	8,130	8,890	9,690	10,460	11,720	12,680			19
											7,850	8,910	9,900	10,820	11,800	12,730	14,270	15,440	16,540		6
											5,180	5,880	6,530	7,140	7,780	8,350	9,420	10,190			31 Dual
650/65 R 38 157 D (160 A8)	**W 18 L** DW 20 B DW 21 B	25.4 26.0 26.4	72.0	31.9	214.4	72	46	434	20	439			7,450	8,060	8,610	**9,100**					40
												7,120	7,830	8,460	9,040	9,550					31
											6,620	7,430	8,170	8,820	9,430	**9,900**					25
											6,950	7,810	8,580	9,260	9,900	10,460					19
											8,460	9,500	10,440	11,280	12,050	12,730	13,650				6
											5,580	6,260	6,890	7,440	7,960	8,400					31 Dual
650/75 R 38 169 D (172 A8)	**DW 21 B** DW 20 B DW 23 B	26.3 25.9 27.0	76.5	34.3	228.1	76	47	453	20	583			8,800	9,650	10,240	10,750	11,960	**12,800**			40
												8,290	9,240	10,120	10,760	11,290	12,560	13,430			31
											7,600	8,640	9,640	10,560	11,210	11,690	13,100	**13,900**			25
											7,980	9,080	10,120	11,090	11,770	12,360	13,750	14,710			19
											9,710	11,060	12,310	13,510	14,340	15,050	16,740	17,900	19,180		6
											6,410	7,300	8,130	8,910	9,470	9,930	11,050	11,820			31 Dual
650/85 R 38 173 D (176 A8)	**DW 23 B** DW 20 B DW 21 B	28.3 27.1 27.5	81.5	36.2	241.3	79	48	550	21	729			9,850	10,790	11,450	12,020	13,400	**14,300**			40
												9,280	10,340	11,330	12,030	12,620	14,060	15,050			31
											8,500	9,680	10,780	11,820	12,550	13,230	14,660	**15,700**			25
											8,930	10,170	11,320	12,410	13,170	13,830	15,400	16,480			19
											10,870	12,370	13,780	15,120	16,040	16,820	18,740	20,070	21,500		6
											7,180	8,170	9,100	9,980	10,580	11,110	12,370	13,240			31 Dual
710/70 R 38 166 D (169 A8)	**DW 23 B** DW 25 B	29.0 29.8	77.1	34.3	227.6	79	47	620	20	647			9,490	10,410	11,090	**11,700**					40
												8,940	9,970	10,930	11,640	12,270					31
											8,190	9,330	10,400	11,400	12,150	**12,800**					25
											8,610	9,800	10,910	11,960	12,760	13,440					19
											10,470	11,930	13,290	14,560	15,530	16,360	17,530				6
											6,910	7,870	8,780	9,610	10,240	10,790					31 Dual
710/70 R 38 171 D (174 A8)	**DW 23 B** DW 25 B	29.0 29.8	77.1	34.3	227.6	79	47	620	20	669			9,490	10,410	11,090	11,690	12,800	**13,600**			40
												8,940	9,970	10,930	11,640	12,270	13,440	14,240			31
											8,190	9,330	10,400	11,400	12,150	12,790	14,010	**14,800**			25
											8,610	9,800	10,910	11,960	12,760	13,440	14,720	15,600			19
											10,470	11,930	13,290	14,560	15,530	16,360	17,920	18,990	20,340		6
											6,910	7,870	8,780	9,610	10,240	10,790	11,830	12,540			31 Dual
800/70 R 38 173 D (176 A8)	**DW 25 B** DW 27 B	30.1 31.0	80.8	35.9	239.8	78	48	682	19	786			11,440	12,550	13,380	**14,300**					40
												10,780	12,020	13,170	14,060	14,820					31
											9,880	11,250	12,540	13,740	14,660	**15,700**					25
											10,370	11,820	13,160	14,430	15,390	16,230					19
											12,630	14,390	16,030	17,560	18,740	19,760	21,720				6
											8,330	9,490	10,570	11,600	12,370	13,040					31 Dual
800/70 R 38 178 D (181 A8)	**DW 25 B** DW 27 B	30.1 31.0	80.8	35.9	239.8	78	48	682	19	798			11,440	12,550	13,380	14,110	15,510	**16,500**			40
												10,780	12,020	13,170	14,060	14,820	16,290	17,360			31
											9,880	11,250	12,540	13,740	14,660	15,460	16,990	**18,200**			25
											10,370	11,820	13,160	14,430	15,390	16,230	17,840	19,020			19
											12,630	14,390	16,030	17,560	18,740	19,760	21,720	23,150	24,810		6
											8,330	9,490	10,570	11,600	12,370	13,040	14,340	15,280			31 Dual

SFT – Technical data and load capacities (Continuation)

Tire size Service description LI/SS	Permitted rims*	Tire section width (inch)	Tire outer dia-meter (inch)	Static loaded radius (inch)	Rolling circum-ference (inch)	Tread depth (32nd)	RCI	Flat plate (sq. inch)	Number of lugs x 2	Tire weight (lbs)	Tire load capacity (lbs) at tire pressure (psi)										Speed (mph)
											9	12	15	17	20	23	29	35	41	47	
900/60 R 38 172 D (175 A8)	**DW 27 B** DW 30 B	34.3 35.4	81.1	36.1	240.7	79	48	698	19	884			10,750	11,740	12,840	**13,900**					40
												10,170	11,290	12,340	13,480	14,590					31
											9,340	10,600	11,770	12,870	14,060	**15,200**					25
											9,810	11,140	12,360	13,510	14,760	15,980					19
											11,940	13,550	15,050	16,450	17,980	19,450	20,840				6
											7,880	8,940	9,930	10,860	11,860	12,830					31 Dual
900/60 R 38 178 D (181 A8)	**DW 27 B** DW 30 B	34.3 35.4	81.1	36.1	240.7	79	48	713	19	886			10,750	11,740	12,840	13,890	15,400	**16,500**			40
												10,170	11,290	12,340	13,480	14,590	16,170	17,360			31
											9,340	10,600	11,770	12,870	14,060	15,210	16,870	**18,200**			25
											9,810	11,140	12,360	13,510	14,760	15,980	17,720	19,020			19
											11,940	13,550	15,050	16,450	17,980	19,450	21,560	23,150	24,810		6
											7,880	8,940	9,930	10,860	11,860	12,830	14,230	15,280			31 Dual
580/85 R 42 163 D (166 A8)	**W 18 L** DW 20 B DW 21 B	22.3 23.1 23.5	80.5	36.2	240.2	73	48	457	22	530			7,950	8,700	9,710	**10,700**					40
												7,510	8,350	9,130	10,210	11,290					31
											6,890	7,830	8,710	9,530	10,640	**11,700**					25
											7,240	8,220	9,140	10,000	11,180	12,360					19
											8,810	10,010	11,140	12,170	13,600	15,050	16,010				6
											5,810	6,600	7,340	8,040	8,990	9,930					31 Dual
580/85 R 42 168 D (171 A8)	**W 18 L** DW 20 B DW 21 B	23.2 24.0 24.4	80.7	36.2	240.2	73	48	457	22	535			7,950	8,700	9,710	10,750	11,630	**12,300**			40
												7,510	8,350	9,130	10,210	11,290	12,220	12,970			31
											6,890	7,830	8,710	9,530	10,640	11,690	12,730	**13,600**			25
											7,240	8,220	9,140	10,000	11,180	12,360	13,350	14,200			19
											8,810	10,010	11,140	12,170	13,600	15,050	16,280	17,290			6
											5,810	6,600	7,340	8,040	8,990	9,930	10,750	11,410			31 Dual
650/75 R 42 165 D (168 A8)	**DW 21 B** DW 20 B DW 23 B	25.6 25.2 26.4	80.1	35.6	239.8	77	48	512	21	587			9,210	10,090	10,770	**11,400**					40
												8,680	9,660	10,600	11,300	11,930					31
											7,950	9,040	10,080	11,050	11,790	**12,300**					25
											8,350	9,490	10,580	11,600	12,380	13,060					19
											10,150	11,570	12,890	14,120	15,070	15,900	17,030				6
											6,700	7,640	8,500	9,330	9,940	10,500					31 Dual
680/80 R 42 180 D (183 A8)	**DW 21 B** DW 20 B DW 23 B	26.0 25.6 26.8	85.0	38.0	252.0	77	49	543	22	802			9,910	10,850	11,880	12,790	14,150	15,210	16,520	**17,600**	40
												9,590	10,410	11,390	12,480	13,430	14,850	15,980	17,340	18,520	31
											9,020	10,010	10,850	11,870	13,010	14,000	15,490	16,660	18,080	**19,300**	25
											9,470	10,510	11,400	12,480	13,670	14,710	16,760	17,500	19,000	20,290	19
											10,710	11,880	12,890	14,110	15,460	16,630	18,400	19,780	21,470	22,930	6
											7,070	8,450	9,160	10,020	10,980	11,820	13,060	14,060	15,260	16,290	31 Dual
710/70 R 42 173 D (176 A8)	**DW 23 B** DW 25 B	28.8 29.6	81.5	36.8	242.1	79	48	527	21	764			9,920	10,880	11,650	12,350	13,450	**14,300**			40
												9,360	10,420	11,420	12,240	12,970	14,120	15,050			31
											8,570	9,760	10,870	11,920	12,770	13,560	14,730	**15,700**			25
											9,000	10,240	11,420	12,510	13,410	14,200	15,470	16,480			19
											10,960	12,470	13,900	15,240	16,320	17,290	18,830	20,070	21,500		6
											7,230	8,240	9,170	10,050	10,770	11,410	12,430	13,240			31 Dual
710/75 R 42 175 D (178 A8)	**DW 23 B** DW 25 B	29.6 30.4	85.5	38.2	254.3	81	49	558	22	798			10,550	11,570	12,440	13,230	14,290	**15,200**			40
												9,940	11,080	12,150	13,060	13,890	15,010	15,980			31
											9,110	10,360	11,550	12,670	13,620	14,330	15,640	**16,500**			25
											9,570	10,890	12,140	13,300	14,310	15,210	16,430	17,500			19
											11,640	13,250	14,770	16,200	17,420	18,520	20,000	21,300	22,820		6
											7,680	8,750	9,750	10,690	11,500	12,230	13,210	14,060			31 Dual
900/60 R 42 180 D (183 A8)	**DW 27 B** DW 30 B	33.9 35.0	84.6	38.2	253.5	79	49	744	20	939			11,230	12,270	13,530	14,770	16,250	**17,600**			40
												10,620	11,800	12,890	14,210	15,510	17,060	18,520			31
											9,760	11,070	12,290	13,440	14,820	16,170	17,790	**19,300**			25
											10,240	11,620	12,910	14,110	15,560	16,990	18,690	20,290			19
											12,470	14,160	15,720	17,180	18,940	20,680	22,740	24,700	26,460		6
											8,220	9,340	10,390	11,340	12,500	13,650	15,010	16,290			31 Dual
710/65 R 46 174 D (177 A8)	**DW 23 B** DW 25 B	27.6 28.3	82.3	37.2	244.9	79	49	566	21	698			9,340	10,090	10,760	11,360	12,560	13,560	**14,800**		40
												8,920	9,800	10,600	11,300	11,930	13,190	14,240	15,510		31
											8,280	9,310	10,230	11,050	11,790	12,440	13,750	14,770	**16,100**		25
											8,700	9,770	10,740	11,600	12,380	13,060	14,440	15,600	16,990		19
											10,580	11,900	13,080	14,120	15,070	15,900	17,570	18,990	20,680		6
											6,990	7,850	8,620	9,330	9,940	10,500	11,600	12,540	13,650		31 Dual
IF 710/65 R 46 183 D	**DW 25 B** DW 27 B	28.2 29.0	82.3	37.2	244.9	79	49	558	21	733			10,200	11,360	12,510	13,560	14,990	16,100	17,640	**19,300**	25–40
													10,610	11,810	12,950	14,100	15,590	16,740	18,350	20,070	19
													11,730	13,050	14,320	15,590	17,240	18,510	20,290	22,190	6
													8,970	9,990	11,010	11,930	13,200	14,170	15,520	16,980	25–40 Dual

* Further admissible rims on request.

Load values given for 6 psi and for 9 psi at 25 mph are for calculating dual and triple load values only. | All load values are for maximum indicated speeds at low torque.| 19 mph (up to 25 mph) load values also apply for low-speed high-torque field work.| For plowing with single driven tires in the furrow, a minimum inflation pressure of 12 psi is required.| For intensive road transport at 40/31/25/19 mph the pressure must be increased by 6 psi.| Maximum inflation pressure should never be exceeded.| All load-speed-pressure data are valid for ground slopes up to and including 20 %.| When operating on slopes greater than 20 %, please, contact Mitas.| Tubeless tires – may be used with a tube.

Trelleborg Wheel Systems Americas, Inc.
570 Trelleborg Drive, Spartanburg, SC 29301
Toll Free Phone Number: 1-866-633-8473
www.mitas-tires.com/en-us

SFT (Super Flexion Tire)

Tires made for High Horsepower Tractors

Mitas Agricultural Radial Tires

mitas-tires.com

kW	22	44	66	88	110	132	162	191	>220
hp	30	60	90	120	150	180	220	260	>300

SFT (R-1W)

SFT (Super Flexion Tire)

Maximum load capacity and traction for powerful machines

- Developed for use on **high-horsepower tractors (> 180 hp) and combines** where performance and reliability are essential.
- Strong flexible sidewalls allow low inflation pressures **for high load-carrying capacities,** gentle ground handling and higher yields.
- **Maximum traction and outstanding productivity** thanks to transport speeds of up to 40 mph and a large contact area.

Conventional radial tire

Mitas SFT radial tire

Tire sidewall flexibility
Strong flexible sidewalls deliver higher load capacity at the lowest possible inflation pressures for better traction and optimum soil protection, even with the heaviest equipment.

SFT – Technical data and load capacities

Tire size / Service description LI/SS	Permitted rims*	Tire section width (inch)	Tire outer diameter (inch)	Static loaded radius (inch)	Rolling circumference (inch)	Tread depth (32nd)	RCI	Flat plate (sq. inch)	Number of lugs x 2	Tire weight (lbs)	Tire load capacity (lbs) at tire pressure (psi)										Speed (mph)
											9	12	15	17	20	23	29	35	41	47	
1000/50 R 25 178 A8 (172 D)	**36.0 TH** 36.0 VA	40.2	65.2	29.1	194.1	76	43	721	14	787			7,650	8,610	9,600	10,560	11,810	12,650	**13,900**		40
												7,560	8,500	9,570	10,660	11,730	13,120	14,050	15,440		31
												8,450	9,370	10,540	11,620	12,790	14,210	15,210	**16,500**		25
												8,880	9,830	11,070	12,220	13,440	14,920	15,980	17,500		19
												10,030	11,120	12,510	13,810	15,190	16,870	18,060	19,780		6
												12,250	13,580	15,280	16,860	18,540	20,610	22,060	23,980		9 Cycl
620/75 R 26 166 A8 (166 B)	**DW 20 B**	24.6	62.6	27.1	183.5	71	43	419	17	412			6,250	7,030	7,820	8,540	9,440	9,920	11,010	**11,700**	31
												5,470	6,250	7,030	7,820	8,540	9,440	9,920	11,010	**11,700**	25
												5,850	6,690	7,530	8,370	9,140	10,100	10,620	11,790	12,500	19
												6,730	7,700	8,650	9,610	10,510	11,610	12,200	13,540	14,380	12
												7,110	10,000	9,150	12,500	11,110	12,270	12,900	14,310	15,190	6
												7,930	9,060	10,200	11,330	12,390	13,680	14,390	15,960	16,950	9 Cycl
750/65 R 26 166 D (169 A8)	**DW 23 B** DW 25 B	29.1 29.8	63.8	28.3	189.0	71	43	496	17	498			7,950	8,590	9,160	9,650	10,750	**11,700**			40
												7,600	8,350	9,020	9,610	10,130	11,290	12,270			31
											7,060	7,930	8,710	9,400	10,020	10,470	11,770	**12,800**			25
											7,410	8,320	9,150	9,880	10,530	11,090	12,360	13,440			19
											9,020	10,130	11,140	12,030	12,820	13,510	15,050	16,360	17,530		6
											5,950	6,680	7,340	7,940	8,460	8,920	9,930	10,790			31 Dual
750/65 R 26 171 D (174 A8)	**DW 23 B** DW 25 B	29.5 30.3	63.6	28.3	189.0	71	43	512	17	580				8,590	8,970	9,370	10,750	11,690	12,790	**13,600**	40
												7,600	8,300	9,020	9,430	9,850	11,290	12,270	13,430	14,240	31
												7,930	8,670	9,400	9,830	10,260	11,770	12,790	13,890	**14,800**	25
												8,310	9,100	9,880	10,330	10,780	12,360	13,440	14,710	15,590	19
												10,120	11,070	12,030	12,570	13,120	15,050	16,360	17,900	18,990	6
												6,680	7,310	7,940	8,290	8,670	9,930	10,790	11,820	12,540	31 Dual
540/65 R 28 142 D (145 A8)	**W 16 L** W 18 L W 15 L	21.3 22.0 21.3	55.7	24.7	165.7	60	40	310	18	261			4,870	5,260	5,580	**5,840**					40
												4,650	5,120	5,520	5,850	6,140					31
											4,320	4,850	5,340	5,770	6,110	**6,400**					25
											4,540	5,100	5,600	6,050	6,420	6,730					19
											5,520	6,210	6,820	7,360	7,820	8,180	8,760				6
											3,650	4,090	4,500	4,860	5,150	5,400					31 Dual
600/65 R 28 154 D (157 A8)	**W 18 L** DW 20 B	23.9 24.6	58.8	26.1	175.0	66	42	394	18	349			5,740	6,210	6,600	6,950	7,700	**8,250**			40
												5,490	6,030	6,520	6,930	7,300	8,080	8,690			31
											5,090	5,720	6,300	6,790	7,230	7,610	8,420	**9,100**			25
											5,350	6,010	6,600	7,130	7,600	7,990	8,840	9,510			19
											6,520	7,320	8,050	8,690	9,250	9,720	10,770	11,580	12,400		6
											4,300	4,830	5,300	5,730	6,110	6,430	7,110	7,640			31 Dual
600/70 R 28 157 D (160 A8)	**W 18 L** DW 20 B	24.7 25.5	62.0	27.4	183.5	68	42	388	19	389			6,390	7,000	7,450	7,830	8,600	**9,100**			40
												6,020	6,710	7,350	7,830	8,220	9,030	9,550			31
											5,520	6,280	7,000	7,670	8,160	8,540	9,420	**9,900**			25
											5,800	6,590	7,350	8,060	8,570	9,010	9,890	10,460			19
											7,060	8,030	8,950	9,810	10,430	10,960	12,040	12,730	13,650		6
											4,650	5,290	5,910	6,470	6,890	7,230	7,950	8,400			31 Dual
600/70 R 28 161 D (164 A8)	**W 18 L** DW 20 B	24.8 25.6	62.1	27.5	183.9	68	42	388	19	389			6,390	7,000	7,450	7,830	8,600	9,100	**10,200**		40
												6,020	6,710	7,350	7,830	8,220	9,030	9,550	10,710		31
											5,520	6,280	7,000	7,670	8,160	8,540	9,420	9,920	**11,000**		25
											5,800	6,590	7,350	8,060	8,570	9,010	9,890	10,460	11,730		19
											7,060	8,030	8,950	9,810	10,430	10,960	12,040	12,730	14,280		6
											4,650	5,290	5,910	6,470	6,890	7,230	7,950	8,400	9,420		31 Dual
540/65 R 30 150 D (153 A8)	**W 16 L** W 18 L W 15 L	21.6 22.0 21.3	58.5	26.3	174.6	63	42	341	19	286			5,030	5,440	5,740	6,010	6,790	**7,400**			40
												4,810	5,280	5,700	6,030	6,310	7,130	7,760			31
											4,450	5,010	5,500	5,940	6,300	6,620	7,440	**8,050**			25
											4,690	5,260	5,780	6,240	6,620	6,910	7,820	8,500			19
											5,700	6,410	7,030	7,610	8,050	8,410	9,510	10,340	11,080		6
											3,760	4,230	4,650	5,020	5,300	5,550	6,270	6,840			31 Dual
600/70 R 30 152 D (155 A8)	**W 18 L** DW 20 B	24.6 25.4	62.8	27.6	185.0	68	43	465	19	391			6,580	7,210	7,560	**7,850**					40
												6,210	6,910	7,570	7,950	8,220					31
											5,680	6,470	7,210	7,900	8,280	**8,550**					25
											5,960	6,790	7,570	8,300	8,700	9,010					19
											7,270	8,270	9,220	10,100	10,600	10,960	11,740				6
											4,800	5,460	6,090	6,670	6,990	7,230					31 Dual
620/75 R 30 166 D (169 A8)	**W 20 B** W 18 L W 21 B	25.0 24.2 25.4	66.9	29.1	196.1	71	44	488	18	482			6,630	7,450	8,280	9,100	10,040	10,750	**11,700**		40
												6,090	6,960	7,830	8,690	9,550	10,540	11,290	12,270		31
											5,440	6,350	7,250	8,160	9,060	9,960	10,990	11,690	**12,800**		25
											5,710	6,670	7,620	8,570	9,510	10,460	11,540	12,360	13,680		19
											6,460	7,530	8,610	9,690	10,760	11,830	13,050	13,980	16,630	19,180	6
											4,620	5,360	6,120	6,890	7,640	8,400	9,270	9,930	10,790		31 Dual
710/55 R 30 159 D (162 A8)	**DW 23 B**	27.2	59.1	26.5	176.2	71	42	372	16	423			6,190	6,760	7,420	8,050	8,920	**9,650**			40
												5,850	6,490	7,100	7,780	8,460	9,370	10,130			31
											5,380	6,100	6,780	7,410	8,110	8,820	9,770	10,470			25
											5,640	6,410	7,120	7,770	8,520	9,260	10,260	11,090			19
											6,870	7,810	8,670	9,470	10,390	11,270	12,490	13,510	14,480		6
											4,530	5,150	5,710	6,250	6,850	7,440	8,250	8,920			31 Dual
710/60 R 30 162 D (165 A8)	**DW 23 B**	27.9	64.8	28.7	191.7	74	43	380	17	477			6,690	7,310	7,950	8,540	9,670	**10,500**			40
												6,330	7,020	7,670	8,350	8,970	10,150	11,000			31
											5,810	6,590	7,330	8,000	8,700	9,370	10,580	**11,400**			25
											6,110	6,920	7,700	8,410	9,140	9,820	11,110	12,050			19
											7,430	8,430	9,370	10,240	11,120	11,960	13,530	14,660	15,710		6
											4,910	5,570	6,190	6,750	7,340	7,890	8,930	9,680			31 Dual
750/55 R 30 162 D (165 A8)	**DW 23 B**	28.3	62.4	28.0	186.0	71	43	465	17	509			6,750	7,360	8,100	8,820	9,700	**10,500**			40
												6,370	7,080	7,740	8,510	9,260	10,190	11,000			31
											5,850	6,650	7,390	8,070	8,880	9,650	10,630	**11,400**			25
											6,150	6,980	7,750	8,480	9,320	10,140	11,160	12,050			19
											7,490	8,500	9,440	10,320	11,340	12,350	13,580	14,660	15,710		6
											4,940	5,610	6,230	6,810	7,490	8,150	8,960	9,680			31 Dual
800/70 R 32 175 A8 (172 B)	**DW 25 B** DW 27 B	30.0 30.9	76.1	33.3	221.7	69	47	496	22	732			9,220	10,090	11,050	12,020	13,150	**13,900**			31
											8,410	9,340	10,120	11,080	12,140	13,230	14,450	**15,200**			25
											9,010	9,990	10,840	11,860	13,000	14,160	15,470	16,280			19
											9,340	10,360	11,230	12,300	13,480	14,550	16,040	16,890			16
											10,350	11,490	12,460	13,630	14,940	16,270	17,770	18,710			12
											10,940	12,140	13,160	14,410	15,790	17,200	18,790	19,780	22,820		9
											12,190	13,540	14,670	16,060	17,600	19,180	20,960	22,060	24,450		9 Cycl
900/60 R 32 176 A8 (173 B)	**DW 27 B** DW 30 B	33.7 35.0	75.0	33.5	224.4	71	47	543	22	731			9,370	10,250	11,070	12,020	13,120	**14,300**			31
											8,580	9,510	10,300	11,270	12,160	13,230	14,410	**15,700**			25
											9,180	10,180	11,030	12,050	13,010	14,160	15,420	16,750			19
											9,530	10,560	11,430	12,500	13,490	14,690	16,000	17,380			16
											10,560	11,700	12,670	13,860	14,960	16,270	17,730	19,260			12
											11,160	12,370	13,380	14,640	15,810	17,200	18,730	20,350	23,480		6
											12,440	13,790	14,930	16,340	17,630	19,180	20,890	22,700	24,680		9 Cycl